



US008484703B2

(12) **United States Patent**
Kenny et al.

(10) **Patent No.:** **US 8,484,703 B2**
 (45) **Date of Patent:** **Jul. 9, 2013**

(54) **SYSTEMS AND METHODS FOR
 DELEGATION AND NOTIFICATION OF
 ADMINISTRATION OF INTERNET ACCESS**

(75) Inventors: **Shane Kenny**, Acworth, GA (US);
Aaron Kenny, Dallas, GA (US)

(73) Assignee: **McAfee, Inc.**, Santa Clara, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
 patent is extended or adjusted under 35
 U.S.C. 154(b) by 162 days.

(21) Appl. No.: **12/464,504**

(22) Filed: **May 12, 2009**

(65) **Prior Publication Data**

US 2009/0222894 A1 Sep. 3, 2009

Related U.S. Application Data

(63) Continuation of application No. 11/244,542, filed on
 Oct. 6, 2005.

(60) Provisional application No. 60/616,490, filed on Oct.
 6, 2004, provisional application No. 60/646,234, filed
 on Jan. 24, 2005.

(51) **Int. Cl.**
H04L 29/06 (2006.01)

(52) **U.S. Cl.**
 USPC **726/4**; 726/29; 709/224; 709/225

(58) **Field of Classification Search**
 None
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,237,677 A 8/1993 Hirose et al. 395/575
 5,490,216 A 2/1996 Richardson, III
 5,557,742 A 9/1996 Smaha et al.

5,583,940 A 12/1996 Vidrascu et al. 380/49
 5,696,486 A 12/1997 Poliquin et al. 340/506
 5,732,212 A 3/1998 Perholtz et al. 395/200.11
 5,832,212 A 11/1998 Cragun et al. 395/188.01
 5,835,722 A 11/1998 Bradshaw et al. 395/200.55

(Continued)

FOREIGN PATENT DOCUMENTS

DE 19359052 9/1996
 EP 0554182 8/1993

(Continued)

OTHER PUBLICATIONS

"enKoo Remote Access Appliance," Dreaming Tree Technology, Inc.
<http://www.ssltunnel.com/default.asp>, 2 pages, printed from the
 Internet Jun. 14, 2005.

(Continued)

Primary Examiner — Nathan Flynn


Assistant Examiner — Michael R Vaughan

(74) *Attorney, Agent, or Firm* — Patent Capital Group

(57) **ABSTRACT**

Disclosed are systems, methods, and computer readable media for delegating administrative rights to a third party in an Internet access control application comprising receiving a designation of a third party wherein the designation identifies the third party as a recipient of administrative rights in an access control application, and receiving a selection of administrative rights to be associated with the third party. Further, an invitation can be sent, or caused to be sent, to the third party. Acceptance of said invitation can be received. Also, administrative rights can be granted to the third party. The systems, methods, and computer readable media can be operable within a client/server architecture. Also disclosed are systems, methods, and computer readable media for notification of an access policy violation. Also disclosed are systems, methods, and computer readable media for administration of an access control application by a third party and access policy violation notification.

20 Claims, 9 Drawing Sheets



U.S. PATENT DOCUMENTS

5,889,958	A	3/1999	Willens	395/200.59
5,941,996	A	8/1999	Smith et al.	714/47
5,944,782	A	8/1999	Noble et al.	709/202
5,958,010	A	9/1999	Agarwal et al.	709/224
5,987,610	A	11/1999	Franczek et al.	
5,987,611	A	11/1999	Freund	713/201
6,012,100	A	1/2000	Frailong et al.	709/250
6,026,438	A	2/2000	Piazza et al.	709/221
6,035,322	A	3/2000	Ingrassia, Jr. et al.	709/224
6,052,730	A	4/2000	Felciano et al.	709/225
6,073,142	A	6/2000	Geiger et al.	
6,185,613	B1	2/2001	Lawson et al.	709/224
6,219,804	B1	4/2001	Mastrangelo et al.	714/38
6,289,378	B1*	9/2001	Meyer et al.	709/223
6,330,597	B2	12/2001	Collin et al.	709/220
6,397,256	B1	5/2002	Chan et al.	709/229
6,446,119	B1	9/2002	Olah et al.	709/224
6,460,050	B1	10/2002	Pace et al.	
6,502,131	B1	12/2002	Vaid et al.	709/224
6,578,146	B2	6/2003	Johnson	713/189
6,606,659	B1	8/2003	Hegli et al.	
6,615,255	B1	9/2003	Blaszczak	709/220
6,631,363	B1	10/2003	Brown et al.	707/1
6,651,190	B1	11/2003	Worley et al.	714/43
6,671,357	B1	12/2003	Roberts	379/93.02
6,675,193	B1	1/2004	Slavin et al.	709/200
6,895,285	B2	5/2005	Maity	700/27
7,194,464	B2	3/2007	Kester et al.	
7,363,656	B2	4/2008	Weber et al.	
7,406,715	B2	7/2008	Clapper	
7,506,155	B1	3/2009	Stewart et al.	
7,890,642	B2	2/2011	Jones et al.	
7,900,239	B2*	3/2011	Van Someren	726/1
8,010,552	B2	8/2011	Kester et al.	
2002/0049806	A1*	4/2002	Gatz et al.	709/203
2002/0078203	A1	6/2002	Greschler et al.	709/225
2002/0087650	A1*	7/2002	Fagerburg et al.	709/208
2002/0166069	A1*	11/2002	Zendzian	713/201
2002/0174367	A1*	11/2002	Kimmel et al.	713/201
2003/0033450	A1	2/2003	Appleby-Alis	710/8
2003/0110168	A1	6/2003	Kester et al.	
2003/0123465	A1	7/2003	Donahue	370/401
2003/0135382	A1	7/2003	Marjeka et al.	
2003/0207237	A1	11/2003	Giezerman	434/118
2004/0003279	A1*	1/2004	Beilinson et al.	713/200
2004/0158630	A1	8/2004	Chang et al.	709/224
2004/0186989	A1	9/2004	Clapper	
2004/0230530	A1	11/2004	Searl et al.	705/51
2004/0267595	A1	12/2004	Woodings et al.	705/9
2005/0015624	A1	1/2005	Ginter et al.	
2005/0050148	A1	3/2005	Mohammadioun et al.	709/206
2005/0060581	A1	3/2005	Chebolu et al.	713/201
2005/0080897	A1*	4/2005	Braun et al.	709/225
2005/0102407	A1	5/2005	Clapper	
2005/0102510	A1*	5/2005	Patrick et al.	713/166
2005/0138423	A1*	6/2005	Ranganathan	713/201
2005/0177871	A1	8/2005	Roesch et al.	
2005/0183143	A1*	8/2005	Anderholm et al.	726/22
2005/0289226	A1*	12/2005	Mohammed et al.	709/208
2006/0218575	A1	9/2006	Blair	
2007/0179950	A1	8/2007	Kester et al.	
2007/0222589	A1	9/2007	Gorman et al.	
2008/0155685	A1*	6/2008	Beilinson et al.	726/21
2008/0201159	A1	8/2008	Gabrick et al.	705/1
2008/0250484	A1	10/2008	Chong et al.	
2011/0307513	A1	12/2011	Kester et al.	
2012/0089500	A1*	4/2012	Dheer et al.	705/35

FOREIGN PATENT DOCUMENTS

EP	1318468	6/2003
JP	5274177	10/1993
JP	7306800	11/1995
JP	2003-233623	8/2003

OTHER PUBLICATIONS

“GoToMyPC,” <https://www.gotomypc.com/tr/ggp/mb/aw/remote.access.computer-broad/g25ggllp?Target=mm/g25ggllp.tmpl>, 1 page, printed from the Internet Jun. 14, 2005.

“iPrism—Internet Access Management,” 1st—Computer-Networks.co.uk <http://www.1st-computer-networks.co.uk/iprism/htm>, 4 pages, printed from the Internet Jun. 9, 2005.

“My WebEx PC,” <http://www.webex.com/lp/aa.php?type=keyword>, 1 page, printed from the Internet Jun. 14, 2005.

“NetVizor User Manual,” WareSight.com http://www.waresight.com/nv_manual.shtml, 10 pages, printed from the Internet Jun. 9, 2005.

“Remote Computer Access Software,” NetworkStreaming, <http://www.networkstreaming.com/index.htm>, 1 page, printed from the Internet Jun. 14, 2005.

“Remotely Access your PCs + servers from anywhere,” Remotely Anywhere, <http://www.remotelyanywhere.com/dmcc/remotelyaccess.asp>, 1 page, printed from the Internet Jun. 14, 2005.

“Server Monitoring,” ServerMojo.com <http://www.servermojo.com/>, 2 pages, printed from the Internet Jun. 9, 2005.

“SurfControl WebFilter 5.0,” ISAServer.org <http://www.isaserver.org/articles/Review-SurfControl-Web-Filter-ISA-Server-2004.html>, 4 pages, printed from the Internet Jun. 9, 2005.

U.S. Appl. No. 11/244,542, filed Oct. 6, 2005, Shane Kenny, 1. Response to Non-Final Office Action, Dec. 8, 2009, 2. Non-Final Office Action, Jun. 8, 2009.

U.S. Appl. No. 60/616,490, filed Oct. 6, 2004, Shane Kenny.

U.S. Appl. No. 60,646,234, filed Jan. 24, 2005, Shane Kenny.

Spytech Software and Design, Inc., “Spytech Netvizor,” SpyTech Online, Oct. 3, 2003, Internet Archive, <http://web.archive.org/web/20031003021346/http://www.spytech-web.com/>.

USPTO Nonfinal Office Action from U.S. Appl. No. 11/244,542, mailed Jun. 8, 2009 (14 pages).

USPTO Final Office Action from U.S. Appl. No. 11/244,542, mailed Feb. 23, 2010 (10 pages).

USPTO Nonfinal Office Action from U.S. Appl. No. 11/244,542, filed Dec. 8, 2009 (17 pages).

USPTO Response to Jun. 8, 2009 Nonfinal Rejection from U.S. Appl. No. 11/244,542, filed Dec. 8, 2009 (17 pages).

USPTO Response to Feb. 23, 2010 Final Rejection from U.S. Appl. No. 11/244,542, filed Jul. 23, 2010 (13 pages).

USPTO Response to Aug. 2, 2010 Nonfinal Rejection from U.S. Appl. No. 11/244,542, filed Feb. 2, 2011 (10 pages).

USPTO Final Office Action from U.S. Appl. No. 11/244,542, mailed Mar. 17, 2011 (11 pages).

USPTO Jun. 7, 2011 RCE Response to Mar. 7, 2011 Final Office Action from U.S. Appl. No. 11/244,542.

Non-Final Office Action in U.S. Appl. No. 11/244,542 mailed on Mar. 15, 2012.

Response to Non-Final Office Action in U.S. Appl. No. 11/244,542 filed on May 15, 2012.

Notice of Allowance in U.S. Appl. No. 11/244,542 mailed on Jul. 24, 2012.

Request for Continued Examination in U.S. Appl. No. 11/244,542 filed on Oct. 24, 2012.

Notice of Allowance in U.S. Appl. No. 11/244,542 mailed on Nov. 20, 2012.

Request for Continued Examination in U.S. Appl. No. 11/244,542, filed Feb. 19, 2013.

Notice of Allowance received for U.S. Appl. No. 11/244,542, mailed on Mar. 15, 2013, 6 pages.

* cited by examiner




FIG. 1





FIG. 2

FIG. 3






FIG. 5






FIG. 6**FIG. 7**


FIG. 8

FIG. 9






FIG. 10**FIG. 11**

1

SYSTEMS AND METHODS FOR DELEGATION AND NOTIFICATION OF ADMINISTRATION OF INTERNET ACCESS

CROSS REFERENCE TO RELATED PATENT APPLICATIONS

This application is a continuation of U.S. Utility application Ser. No. 11/244,542, filed Oct. 6, 2005 which claims priority to U.S. Provisional Application No. 60/616,490 filed Oct. 6, 2004 and U.S. Provisional Application No. 60/646,234 filed Jan. 24, 2005, all of which are herein incorporated by reference in their entireties.

BACKGROUND OF THE INVENTION

For many years, Internet Access Control applications have existed to allow users to control the type of content that can be accessed through their Internet connection. Additionally, the ability to log all Internet usage of a user or access policy violations has is known. However, in order to view these logs, or be made aware of access policy violations, a user or a third party has to periodically check the logs. This does not permit instant notification of an Internet Access Policy violation. Administration of Internet access control applications is also problematic. Typically, someone with administrative rights controls the settings of an Internet access control application. This can cause an issue if a user of an Internet access control application does not want access to the administration features of the application.

SUMMARY OF THE INVENTION

Disclosed herein are systems, methods, and computer readable media capable of delegating administrative rights to a third party in an Internet access control application comprising receiving a designation of a third party wherein the designation identifies the third party as a recipient of administrative rights in an access control application, and receiving a selection of administrative rights to be associated with the third party. Further, an invitation can be sent, or caused to be sent, to the third party. Acceptance of said invitation can be received. Also, administrative rights can be granted to the third party. The systems, methods, and computer readable media can be operable within a client/server architecture.

Also disclosed are systems, methods, and computer readable media capable of notification of an Internet access policy violation comprising determining if a threshold has been exceeded, determining a notification to send, determining a recipient of the notification, and causing the notification to be sent to the recipient. The notification can also be sent directly by the system. The systems, methods, and computer readable media can be operable within a client/server architecture.

Further disclosed are systems, methods, and computer readable media capable of administering an access control application comprising receiving an administrative command from a third party administrator and modifying administrative settings associated with a user of the access control application based on the administration command. The systems, methods, and computer readable media can be operable within a client/server architecture.

Additional advantages of the invention will be set forth in part in the description which follows. The advantages of the invention will be realized and attained by means of the elements and combinations particularly pointed out in the appended claims. It is to be understood that both the forego-

2

ing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention, as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description, serve to explain the principles of the invention:

FIG. 1 is a block diagram illustrating an exemplary operating environment for performing the disclosed method;

FIG. 2 illustrates in an exemplary networked environment capable of performing the disclosed methods;

FIG. 3 illustrates where an exemplary Internet Access Control client can reside in a computing device;

FIG. 4 illustrates operational steps in an exemplary Internet Access Control application;

FIG. 5 provides exemplary steps involved in handling notifications;

FIG. 6 illustrates exemplary steps involved in delegating administrative control to a third party;

FIG. 7 illustrates exemplary steps involved in removing administrative control from a third party;

FIG. 8 illustrates exemplary steps involved in a third party administrator's control of a user's account;

FIG. 9 illustrates exemplary steps involved in setting a threshold;

FIG. 10 illustrates exemplary steps involved in adding a notification to an Internet Access Control application; and

FIG. 11 illustrates exemplary steps involved in removing a notification from an Internet Access Control application.

DETAILED DESCRIPTION OF THE INVENTION

Before the present methods and systems are disclosed and described, it is to be understood that this invention is not limited to specific synthetic methods, specific components, or to particular compositions, as such may, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting.

As used in the specification and the appended claims, the singular forms "a," "an" and "the" include plural referents unless the context clearly dictates otherwise.

Ranges may be expressed herein as from "about" one particular value, and/or to "about" another particular value. When such a range is expressed, another embodiment includes from the one particular value and/or to the other particular value. Similarly, when values are expressed as approximations, by use of the antecedent "about," it will be understood that the particular value forms another embodiment. It will be further understood that the endpoints of each of the ranges are significant both in relation to the other endpoint, and independently of the other endpoint.

"Optional" or "optionally" means that the subsequently described event or circumstance may or may not occur, and that the description includes instances where said event or circumstance occurs and instances where it does not.

A "category" describes the type of content that a website falls into. For example, playboy.com would fall into a "pornography" category. It is possible that a website may fall into more than one category. For example, playboy.com could be categorized as "pornography", "nudity", "sex", "e-commerce" and "adults only".

"Category Mapping" is a list of categories that a website can fall into. In the example of playboy.com the category

mapping for this website could include “pornography”, “nudity”, “sex”, “e-commerce” and “adults only”.

An “Internet Enabled Application” is any computer application that has the ability to communicate over a network (private or public) through a network-enabling device. An example of this would be Internet Explorer, AOL Instant Messenger, QuickBooks, Microsoft Word, etc.

An “Internet Access Policy” is a set of rules that a user has established as acceptable use of the Internet. This could be specified by a consumer, employer or even governmental body. This policy deems what is appropriate and inappropriate Internet content to access using an Internet enabled device. This policy may even lay out acceptable behavior in regard to use of the Internet. This policy may even be created and enforced by an individual for their personal Internet usage.

A “notifiable website” is a website that violates the Internet Access Policy and has been deemed by a user as being in a category that they would like to be notified about access attempts. For example, the user may specify they want “pornography” and “sports” categories blocked but only request to be notified about “pornography” access attempts. When the computer’s user accesses playboy.com this site is blocked and is deemed notifiable, however when the user visits nascar.com the site is blocked but not deemed as notifiable.

The present invention may be understood more readily by reference to the following detailed description of preferred embodiments of the invention and the Examples included therein and to the Figures and their previous and following description.

This invention relates to providing a user of an Internet Access Control application, also referred to as “access control application,” the ability to have a third party control the settings of the Internet Access Control application. The third party administrator can remotely modify an access control application user’s administrative settings by sending administrative commands, either remotely or locally. As part of the configuration of the Internet Access Control application the user can specify a third party to delegate administrative control to. The method of specifying the third party can vary. By way of example, and not limitation, such methods include using a third party’s email address or a username if the third party is also a user of the Internet Access Control application.

The invention relates to providing notification, or causing a notification to be sent, to a user or an administrative user (third party or otherwise), when administrative changes are made to the Internet Access Control application. Additionally, the invention relates to providing notification, which includes causing notification to be sent, to a user, the user can include an administrative user (third party or otherwise), when a violation, or an attempted violation, of the Internet Access Policy, also referred to as “access policy,” occurs. When configuring the Internet Access Control application, the user can establish a threshold at which the user wishes to be notified of a violation. The threshold may be a number of violations in a set period of time, a certain number of a specific type of violation, and the like. Each time the Internet Access Control application notices a violation of the Access Policy it can keep track of the details of that violation. When a particular threshold is met or exceeded for a user, one or more notifications can be dispatched.

FIG. 1 is a block diagram illustrating an exemplary operating environment for performing the disclosed method. This exemplary operating environment is only an example of an operating environment and is not intended to suggest any limitation as to the scope of use or functionality of operating environment architecture. Neither should the operating envi-

ronment be interpreted as having any dependency or requirement relating to any one or combination of components illustrated in the exemplary operating environment.

The method can be operational with numerous other general purpose or special purpose computing system environments or configurations. Examples of well known computing systems, environments, and/or configurations that may be suitable for use with the system and method include, but are not limited to, personal computers, server computers, laptop devices, and multiprocessor systems. Additional examples include set top boxes, programmable consumer electronics, network PCs, minicomputers, mainframe computers, distributed computing environments that include any of the above systems or devices, and the like.

The method may be described in the general context of computer instructions, such as program modules, being executed by a computer. Generally, program modules include routines, programs, objects, components, data structures, etc. that performs particular tasks or implement particular abstract data types. The system and method may also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both local and remote computer storage media including memory storage devices.

The method disclosed herein can be implemented via a general-purpose computing device in the form of a computer **101**. The components of the computer **101** can include, but are not limited to, one or more processors or processing units **103**, a system memory **112**, and a system bus **113** that couples various system components including the processor **103** to the system memory **112**.

The system bus **113** represents one or more of several possible types of bus structures, including a memory bus or memory controller, a peripheral bus, an accelerated graphics port, and a processor or local bus using any of a variety of bus architectures. By way of example, such architectures can include an Industry Standard Architecture (ISA) bus, a Micro Channel Architecture (MCA) bus, an Enhanced ISA (EISA) bus, a Video Electronics Standards Association (VESA) local bus, and a Peripheral Component Interconnects (PCI) bus also known as a Mezzanine bus. This bus, and all buses specified in this description can also be implemented over a wired or wireless network connection. The bus **113**, and all buses specified in this description can also be implemented over a wired or wireless network connection and each of the subsystems, including the processor **103**, a mass storage device **104**, an operating system **105**, Internet Control Application client **106**, data **107**, a network adapter **108**, system memory **112**, an Input/Output Interface **110**, a display adapter **109**, a display device **111**, and a human machine interface **102**, can be contained within one or more remote computing devices **114a,b,c** at physically separate locations, connected through buses of this form, in effect implementing a fully distributed system.

The computer **101** typically includes a variety of computer readable media. Such media can be any available media that is accessible by the computer **101** and includes both volatile and non-volatile media, removable and non-removable media. The system memory **112** includes computer readable media in the form of volatile memory, such as random access memory (RAM), and/or non-volatile memory, such as read only memory (ROM). The system memory **112** typically contains data such as data **107** and/or program modules such as operating system **105** and Internet Control Application

client **106** that are immediately accessible to and/or are presently operated on by the processing unit **103**.

The computer **101** may also include other removable/non-removable, volatile/non-volatile computer storage media. By way of example, FIG. 1 illustrates a mass storage device **104** which can provide non-volatile storage of computer code, computer readable instructions, data structures, program modules, and other data for the computer **101**. For example, a mass storage device **104** can be a hard disk, a removable magnetic disk, a removable optical disk, magnetic cassettes or other magnetic storage devices, flash memory cards, CD-ROM, digital versatile disks (DVD) or other optical storage, random access memories (RAM), read only memories (ROM), electrically erasable programmable read-only memory (EEPROM), and the like.

Any number of program modules can be stored on the mass storage device **104**, including by way of example, an operating system **105** and Internet Control Application client **106**. Each of the operating system **105** and Internet Control Application client **106** (or some combination thereof) may include elements of the programming and the Internet Control Application client **106**. Data **107** can also be stored on the mass storage device **104**. Data **107** can be stored in any of one or more databases known in the art. Examples of such databases include, DB2®, Microsoft® Access, Microsoft® SQL Server, Oracle®, MySQL, PostgreSQL, and the like. The databases can be centralized or distributed across multiple systems.

A user can enter commands and information into the computer **101** via an input device (not shown). Examples of such input devices include, but are not limited to, a keyboard, pointing device (e.g., a "mouse"), a microphone, a joystick, a serial port, a scanner, and the like. These and other input devices can be connected to the processing unit **103** via a human machine interface **102** that is coupled to the system bus **113**, but may be connected by other interface and bus structures, such as a parallel port, game port, or a universal serial bus (USB).

A display device **111** can also be connected to the system bus **113** via an interface, such as a display adapter **109**. For example, a display device can be a monitor or an LCD (Liquid Crystal Display). In addition to the display device **111**, other output peripheral devices can include components such as speakers (not shown) and a printer (not shown) which can be connected to the computer **101** via Input/Output Interface **110**.

The computer **101** can operate in a networked environment using logical connections to one or more remote computing devices **114a,b,c**. By way of example, a remote computing device can be a personal computer, portable computer, a server, a router, a network computer, a peer device or other common network node, and so on. Logical connections between the computer **101** and a remote computing device **114a,b,c** can be made via a local area network (LAN) and a general wide area network (WAN). Such network connections can be through a network adapter **108**. A network adapter **108** can be implemented in both wired and wireless environments. Such networking environments are commonplace in offices, enterprise-wide computer networks, intranets, and the Internet **115**.

FIG. 2 illustrates in more detail an exemplary networked environment capable of performing the disclosed methods. As shown in FIG. 2, an Internet enabled device **201** is connected to the Internet **115**. Internet enabled device **201**, can be, for example, previously described computer **101**, a cellular phone, a PDA, and the like. An Internet Access Control client application can be resident on the Internet enabled

device **201** and capable of communicating via the Internet **115** with category server **205**, agency server **206**, web server **207**, and notification server **208**. These servers are represented in FIG. 2 as multiple entities for purposes of clarification. However, it is recognized that the tasks associated with each server can be performed by one or more servers. The servers can be, for example, previously described computer **101** and the like. Each server can have one or more databases resident in memory. For example, the category server **205** can store a website category database **202**. The agency server **206** can store a usage logging database **203** and a user information database **204**. It is recognized that the databases can be stored on any server of the present invention and that any of the servers can connect to any of the databases and that any of the servers can communicate with one another.

Category server **205** can assign a category to a website. The agency server **206** can request the category mapping of a website from the category server **205** upon user request. It can connect to the website category database **202**. The website category database **202** can store a category mapping for websites. A website can be categorized into more than one category. The agency server **206** directly communicates with the Internet Access Control client application resident on the Internet enabled device **201**. All communication from the Internet Access Control client application can be routed through the agency server **206**. The agency server **206** can connect to the usage logging database **203** and the user information database **204**. The usage logging database **203** can securely store a user's Internet usage data. It is not required that a user store this data in the usage logging database **203**. The user information database **204** can store data about a user that can be used for managing the user's account. This includes, but is not limited to, contact information, billing information, usage history, Internet Access Control client application software settings, and the like.

The web server **207** provides the web-based portions of the Internet Access Control client application. This web server **207** can connect to the usage logging database **203** and the user information database **204**. The web server **207** can connect to agency server **206** and to the category server **205**. The notification server **208** can send notifications to a user or a non-user, or can cause notifications to be sent to a user or a non-user. These notifications can include emails, SMS text messages, instant messages (IM), pages to a pager, voice messages, and the like. The notification server **208** can, for example, issue a phone call to transmit a voice message over the Internet **115** using a Voice Over IP (VOIP) or through a standard telephone connection, these connections are illustrated by the Internet cloud **115** and network cloud **209**. The voice message can be received by any voice-enabled device **210**. Examples of voice-enabled devices include, VOIP phones, cellular phones, "land line" phones, satellite phones, and the like.

For purposes of illustration, application programs and other executable program components such as the operating system **105** are illustrated herein as discrete blocks, although it is recognized that such programs and components reside at various times in different storage components of the computing device **101**, and are executed by the data processor(s) of the computer. As illustrated in FIG. 3, portions of the Internet Control Application client **106** can reside inside of the UDP **302** and TCP/IP **303** protocol stacks on the user's computer **101**. In doing this the Internet Control Application client **106** can "see" all traffic that comes from a network enabled application **301** that is destined for the Internet **115** or private network via network adapter **108**.

7

An implementation of Internet Control Application client **106** may be stored on or transmitted across some form of computer readable media. Computer readable media can be any available media that can be accessed by a computer. By way of example, and not limitation, computer readable medium may comprise "computer storage media" and "communications media." "Computer storage media" include volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, program modules, or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by a computer.

The processing of the disclosed method can be performed by software components. The disclosed method may be described in the general context of computer-executable instructions, such as program modules, being executed by one or more computers or other devices. Generally, program modules include computer code, routines, programs, objects, components, data structures, etc. that performs particular tasks or implement particular abstract data types. The disclosed method may also be practiced in grid-based and distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both local and remote computer storage media including memory storage devices.

FIG. 4 illustrates steps in an exemplary Internet Access Control application involving a client and a server. Beginning at block **401**, the Internet Access Control client application is started. At **402**, a check is performed to determine if the user has requested retrieval of a website via a network enabled application. If no request has been made, the system returns to block **402**. Internet Access Control client application will remain in a wait-state until Internet traffic is sensed. Once traffic is sensed Internet Access Control client application will activate and begin processing the traffic. If a request has been made, the system proceeds to block **403** and performs a check to determine if the user is logged in. When Internet traffic is sensed Internet Access Control client application needs to enforce restrictions on the user that is using the computer. As such, the user needs to be determined. If Internet Access Control client application already knows which user is logged in then the system proceeds to block **405** to continue with processing of traffic. If the user is not known, the system proceeds to block **404** to log in the user. The system can prevent all network activity until the user is logged in.

Once the user is logged in, or it is established that the user is already logged in, the system proceeds to block **405**. At block **405**, the system retrieves the category of the website requested from agency server **206**, which in turn requests the category mapping from category server **205**. Then at block **406**, the system can test the retrieved category against the list of restricted categories associated with the logged-in user. At block **408**, if the category is blocked by the user's category restrictions, the website will be blocked. The user can be notified why the website has been restricted. At block **407**, if the category is not blocked by the user's category restrictions, the website will be allowed. Once the website is blocked or allowed, the system proceeds to block **409**.

8

At block **409**, the system performs a check to determine if usage is logged. Usage logging can include recording websites visited, websites attempted to visit, and the like. If usage logging is enabled, either by the user or by an administrative user (this can be the same or different users), the system proceeds to create and store a log of the website visited or attempted to visit at block **410**. The log can be stored locally on the user's computer or the log can be stored in the usage logging database **203** and accessed by the agency server **206** and web server **207**. If usage logging is not enabled, or once usage logging is completed, the system proceeds to block **411**. At block **411**, a check is performed to determine if notifications are enabled. If notifications are not enabled, the system returns to block **402** to wait for the next Internet traffic request. If notifications are enabled the system proceeds to block **412** to handle notifications. A flowchart illustrating exemplary steps in handling notifications can be found in FIG. 5 and described below. Once notifications are handled, the system returns to block **402** to wait for the next Internet traffic request.

FIG. 5 provides exemplary steps involved in handling notifications. At block **501**, the handle notification starts and proceeds to block **502**. At block **502**, a check is performed to determine if the current website is notifiable. The user or an administrative user (this can be the same or different users) can set which category, or categories, of websites are notifiable. If the current website is not notifiable, the system proceeds to block **510** and ends notification handling. If the current website is notifiable, the system proceeds to increment an alert counter at block **503**. The alert counter tracks the number of sites that are notifiable for a user. Additionally, the timeframe in which the attempted website retrievals have occurred in can be recorded. Other parameters known to those skilled in the art can be used to track notifications.

The system then proceeds to block **504** and performs a check to determine whether a threshold has been reached. The system can review the websites that have been marked as notifiable and determine if a threshold has been tripped that will generate a notification to be sent, or cause the sending of a notification. This determination can be made by a user configurable set of parameters. These parameters can include any combination of the following factors: the number of notifiable sites encountered, the timeframe the attempted website retrievals occur in, the category of the website, and the like. If a threshold has not been reached, the system proceeds to block **510** and ends notification handling. If a threshold has been reached, the system proceeds to block **505**.

At block **505**, the system determines if there are notifications to send. When a threshold has been reached the system determines if notifications have been setup by a user. The Internet Access control application user can enable notifications and configure a notification list as illustrated in FIG. 10 and described below. If there are no notifications to send or notification is not enabled, the system proceeds to block **510** and ends notification handling. If there are notifications to send, the system proceeds to block **506**. At block **506**, the system reviews a list of notifications, and loads the first notification in the list. The system then proceeds to block **507** and sends the notification through the notification server **208**, or in the alternative, causes the notification to be sent. For example, the system can use an Internet access control client application to send an email directly from a user's computer, or an instant message directly from the user's instant message software. At this step, the notification is formatted and sent according to the type of notification. For example, the notification can be an email, SMS text message, instant message (IM), page to a pager, voice message, and the like. After the

notification is sent the system proceeds to block **508** to determine if there are more notifications remaining in the notification list. If there are more notifications in the notification list, the system proceeds to block **509** and loads the next notification from the notification list. The system then returns to block **507** and sends the next notification. If there are no more notifications in the notification list, the system proceeds to block **510** and ends notification handling.

As described herein a user of the Internet Control application can designate a third party to serve as a third party administrative user. A third party administrative user can modify various settings for the user. These settings include, but are not limited to, thresholds, notifications, restricted categories, and the like. The third party administrator can modify the user's Internet Access Control application settings remotely via the Internet, as the user's Internet Access Control client application settings can be stored in User Information Database **204** and made accessible to a server, for example, agency server **206**. When the user delegates administrative control to a third party the third party can be sent an invitation via email. This invitation must be accepted before the third party can have administrative control of the user's account. This emailed invitation will instruct the third party on how to create an account, allowing the third party to access the administrative controls of the Internet Access Control Application on behalf of the user. (If the third party has already created an account for use with another user of the Internet Access Control Application, the same account can be used and the new user's administrative controls attached.)

FIG. **6** illustrates exemplary steps involved in delegating administrative control to a third party. At block **601**, adding delegation starts and the system proceeds to block **602**. At block **602**, the user inputs, for example, an email address of the third party that the user would like to delegate administration of their Internet Access Control application settings to. Other means for identifying a third party are specifically contemplated, such as username, unique identifier, telephone number, and the like. Then, at block **603** the user sets delegation parameters for the third party. Such parameters can include, but are not limited to, full access, threshold setting, category setting, notification setting, and the like. Then at block **604** the third party and associated delegation parameters are saved and at block **605** an invitation is sent to the third party by email, for example. Other means for sending an invitation to a third party are specifically contemplated, such as, voice message, SMS text message, instant message (IM), page to a pager, and the like. The system then proceeds to block **606** and terminates adding a third party administrator.

FIG. **7** illustrates exemplary steps involved in removing administrative control from a third party. At block **701**, removing delegation starts and the system proceeds to block **702**. At block **702**, the users select the third party administrator to remove delegated rights from. Then, at block **703**, the system can confirm the user's selection. If the user does not confirm the selection, the system proceeds to block **705** and terminates third party administrator removal. If the user confirms the selection, the system proceeds to block **704** to remove delegation. Removing delegation can include, but is not limited to, complete removal of all delegated control or removal of selected feature of control, such as threshold setting, category setting, notification setting, and the like. The system then proceeds to block **705** and terminates third party administrator removal.

Once an invitation to be a third party administrator has been accepted, the third party can log in and control the user's account. The third party can have varying degrees of control over the user's account, from limited control to full control. In

addition, the third party can have the ability to restrict the user's access to certain administrative settings in the administrative controls. Should the original user attempt to access any area that the third party has restricted, they will be presented with a message informing them that access to the area has been restricted and a notification can be sent to the third party administrative user.

FIG. **8** illustrates exemplary steps involved in a third party administrator's control of a user's account. At block **801**, using delegation starts and the system proceeds to block **802**. At block **802**, the third party administrator logs in to verify that they have the authority to control the user's account. If the third party administrator cannot log in then access will not be allowed. Once the third party administrator has successfully logged in, the system proceeds to block **803** where the third party administrator can select the account of the Internet Access Control application user to administer. A third party administrator can have delegated authority from one or more Internet Access Control application users. Once the third party administrator has selected an account to administer, the system proceeds to block **804** where the third party administrator can edit the user's Internet Access Control application settings. The third party administrator can prevent user access to features within the Internet Access Control application administration area that the user previously had access to. The third party administrator can have access to all areas that the Internet Access Control application user has access to as the administrator. This means the third party administrator can change all of the Internet Access Control application settings including passwords and which categories are blocked or allowed. Third party administrators are typically not allowed access to areas containing financial information of the user. The third party administrator can also "lock" users out of certain administrative functions, preventing the user from accessing those functions. When the third party administrator chooses to lock access to certain administrative functions they can limit access to one or more of any administrative feature. When the third party administrator is done editing the user's Internet Access Control application settings, the system proceeds to block **805** and terminates third party administration.

The threshold is how the Internet Access Control application determines that it needs to send notifications. The threshold can be the number of notifiable websites visited in a certain time period or the number of notifiable websites visited without time period. (Visited also encompasses "Attempts" even if the website was blocked.) There could be other factors affecting the threshold like time of day, severity of websites visited or attempted, the currently logged in user, and the like. The admin can also specify the categories that are notifiable since these can differ from the categories that are blocked and allowed. The admin can also specify the times of day that specific notifications can be sent. For instance, a phone notification may be sent during daytime hours but not at night, an email notification may be sent anytime of the day or only when the Internet Access Control application user knows the recipient is at work.

FIG. **9** illustrates exemplary steps involved in setting a threshold. At block **901**, setting threshold starts and the system proceeds to block **902**. At block **902**, after logging in if not already logged in, the user (can be a third party administrator) sets threshold parameters that will determine when a notification will be sent. Threshold parameters can include, the number of notifiable site viewing attempts and the timeframe in which the notifiable site viewing attempts occurred. Then at block **903**, the system validates the parameters to ensure that they are within reasonable bounds. For example

11

the number of notifiable websites cannot be infinite and the timeframe will most likely not be website access attempts in a one year period, etc. Then at block 904, the threshold parameters are saved and the system proceeds to block 905 to terminate threshold setting.

As described earlier, once a threshold has been reached a notification can be sent. Additionally, when an administrative change has been made, or attempted, a notification can be sent. These notifications can be sent to anyone designated by the user, the third party administrator, or both. Notifications can generally be sent to any device capable of receiving a communication signal. These notifications can include, but are not limited to, emails, SMS text messages, instant messages (IM), pages to a pager, voice messages, and the like. Notification can also be made, for example, to a third party application that allows plug-ins. An example can be a custom toolbar for Internet Explorer.

Notification methods and contacts are configured in the Internet Access Control application. Multiple notifications can be applied to each threshold, and thresholds can be set per user. This allows the notification process to be customized for every user of the Internet Access Control application. The notifications can be scheduled such that an administrator may wish to have pager notifications sent out during all hours, but only send phone call notifications from 9:00 am to 5:00 pm. This allows the administrator to further fine tune the notification process.

The notifications can contain information to identify the person who violated the access policy, and can contain additional information about the actual violations or how the violator can best be contacted. Optionally with notification methods implementing 2-Way communication, such as a voice phone call, the administrator can immediately suspend Internet Access for the user who is violating the Access Policy. For example, in the case of a phone call (voice message) notification, the recipient of the notification may be prompted to "Press 1 to disable Internet access now". After pressing 1, they may be asked to enter a password before the Internet Access would be disabled for the violating user. This system allows for immediate notification of Internet Access Policy violations regardless of whether the recipient is at a computer and allows for modification of the user's access rights remotely without requiring the recipient to be at a computer.

FIG. 10 illustrates exemplary steps involved in adding a notification to an Internet Access Control application. At block 1001, adding notification starts and the system proceeds to block 1002. At block 1002, after logging in if not already logged in, the user (can be a third party administrator) can select the type of notification to configure from a list of pre-defined notifications. Then at block 1003, the user can enter notification parameters. Based on the type of notification the user is configuring they can be prompted to enter the parameters required to make the notification work. Each notification type can have its own unique set of parameters that are needed in order to make it function. For example, for voice notification, the user will have to enter a notification recipient phone number. At block 1004, the notification parameters can be validated to ensure they parameters are accurate. For example, the phone number would need to be 10 digits or an email address would need to conform to a user@host.com standard. Then at block 1005, the notification and associated parameters are saved to a notification list. The system then proceeds to terminate adding a notification at block 1006.

FIG. 11 illustrates exemplary steps involved in removing a notification from an Internet Access Control application. At block 1101, removing notification starts and the system pro-

12

ceeds to block 1102. At block 1102, after logging in if not already logged in, the user (can be a third party administrator) can select the notification to remove from a list of established notifications. Then the system performs a check at block 1103 to confirm the user's selection. If the user does not confirm the selection, the system proceeds to block 1105 and terminates notification removal. If the user confirms the selection, the notification is removed from the list of established notifications at block 1104. The system then proceeds to block 1105 and terminates notification removal.

While this invention has been described in connection with preferred embodiments and specific examples, it is not intended that the scope of the invention be limited to the particular embodiments set forth, as the embodiments herein are intended in all respects to be illustrative rather than restrictive.

Unless otherwise expressly stated, it is in no way intended that any method set forth herein be construed as requiring that its steps be performed in a specific order. Accordingly, where a method claim does not actually recite an order to be followed by its steps or it is not otherwise specifically stated in the claims or descriptions that the steps are to be limited to a specific order, it is no way intended that an order be inferred, in any respect. This holds for any possible non-express basis for interpretation, including: matters of logic with respect to arrangement of steps or operational flow; plain meaning derived from grammatical organization or punctuation; the number or type of embodiments described in the specification.

Throughout this application, various publications are referenced. The disclosures of these publications in their entireties are hereby incorporated by reference into this application in order to more fully describe the state of the art to which this invention pertains.

It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the scope or spirit of the invention. Other embodiments of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the invention being indicated by the following claims.

What is claimed is:

1. A computer-implemented method of delegating administrative rights to a third party comprising:
 - receiving, from a first computing device, a request, by a first end user associated with a first account of a network access control application, to delegate administrative rights for the first account of the network access control application to a third party end user, wherein the request identifies the third party end user, and the access control application monitors violations of a network access policy by a particular set of end users of at least one network-enabled application, the particular set of end users associated with the first account, wherein the third party end user is outside the particular set of end users associated with the first account;
 - receiving a selection, specified by the first end-user, of particular administrative rights in the network access control application to delegate to the third party end user;
 - causing an invitation to be sent to the third party end user for acceptance by the third party end user of the delegation of the particular administrative rights for the first account; and

13

providing the third party end user the particular administrative rights for the first account of the access control application.

2. The method of claim 1, wherein sending of the invitation is triggered by the request.

3. The method of claim 2, further comprising: receiving acceptance of the invitation from the third party end user; and wherein the particular administrative rights for the first account of the access control application are provided to the third party end user in response to the received acceptance.

4. The method of claim 1, further comprising: providing the third party end user administrative rights in the access control application.

5. The method of claim 1 further comprising: receiving a request, from a remote second computing device, for the third party end user to perform an administrative command relating to the first account of the network access control application; and modifying settings of the network access control application associated with the first account based at least in part on the administration command.

6. The method of claim 5, wherein the request is received from a remote second computing device.

7. The method of claim 1, wherein the invitation includes instructions for creating an administrator account for the third party end user for use in performing administrative commands relating to settings for the first account of the network access control application.

8. The method of claim 1, wherein the delegated particular administrative rights, prior to delegation to the third party end user, are associated with the first end user.

9. The method of claim 8, wherein delegating the particular administrative rights removes at least some of the delegated particular administrative rights from the first end user.

10. The method of claim 1, wherein a second data record identifies that administrative rights for a second account of the network access control application have been delegated to another third party end user.

11. The method of claim 1, wherein the first end user associated with the first account is an end user of the at least one network-enabled application.

12. A system of delegating administrative rights to a third party comprising:

a server device serving at least a portion of an access control application in communication with at least one network-enabled application residing, at least in part, on a client computing device, the access control application including:

a network access control module configured to monitor violations of a network access policy associated with a first account by a particular set of end users of the at least one network-enabled application, the particular set of end users associated with the first account; and an administrative rights manager configured to:

receive, from a remote computing device, a request, by a first end user in the particular set of end users associated with the first account of the access control application, to delegate administrative rights for the first account of the access control application to a third party end user outside the particular set of end users associated with the first account;

14

receive a selection, specified by the first end-user, of particular administrative rights in the access control application, for the first account, to delegate to the third party end user;

cause an invitation to be sent to the third party end user for acceptance by the third party end user of the delegation of the particular administrative rights for the first account; and

provide the third party end user the particular administrative rights for the first account of the access control application.

13. The system of claim 12, wherein the administrative rights manager is further configured to:

receive an administrative command from the third party end user; and

modify settings of the network access control application associated with the first account based at least in part on the administration command.

14. The system of claim 13, wherein the settings associated with the first account include a set of restricted categories of content.

15. The system of claim 13, wherein the settings associated with the first account include a set of rules defining notification of attempts to access restricted content using the at least one network-enabled application.

16. The system of claim 15, wherein the set of rules define a threshold frequency of attempts to access restricted content, and meeting the defined threshold triggers a notification.

17. A non-transitory computer readable medium having computer executable instructions embodied thereon for delegating administrative rights to a third party comprising:

receiving, from a first computing device, a request, by a first end user associated with a first account of a network access control application, to delegate administrative rights for the first account of the network access control application to a third party end user, wherein the request identifies the third party end user, and the access control application monitors violations of a network access policy by a particular set of end users of at least one network-enabled application, the particular set of end users associated with the first account, wherein the third party end user is outside the particular set of end users associated with the first account;

receiving a selection, specified by the first end-user, of particular administrative rights in the network access control application to delegate to the third party end user;

causing an invitation to be sent to the third party end user for acceptance by the third party end user of the delegation of the particular administrative rights for the first account; and

providing the third party end user the particular administrative rights for the first account of the access control application.

18. The non-transitory computer readable medium of claim 17, wherein the network access policy is an internet content access policy and the at least one network-enabled application is an internet-enabled application.

19. A non-transitory computer readable medium having computer executable instructions embodied thereon for administering a network access control application comprising:

identifying a request, by a first end user associated with a first account of a network access control application, to delegate administrative rights for the first account of the network access control application to a third party end user;

causing an invitation to be sent to the third party end user for acceptance by the third party end user of the delegation of the particular administrative rights for the first account;

providing the third party end user the particular administrative rights for the first account of the access control application upon acceptance of the delegation of the particular administrative rights for the first account;

authenticating, the third party end user to perform particular administrative commands to change settings of the first account of the network access control application;

receiving a particular administrative command from the authenticated third party administrator end user; and

modifying settings of the network access control application associated with the first account based at least in part on the administration command;

wherein the network access control application monitors violations of a network access policy associated with the first account by a particular set of end users of at least one network-enabled application, the particular set of end users associated with the first account, and the third party end user is outside the particular set of end users associated with the first account.

20. The computer readable medium of claim **19** wherein the particular end user associated with the first account is an end user of the at least one network-enabled application and included in the particular set of end users.

* * * * *